

TITLE OF THE INVENTION

COAXIAL FULL-FLOW AND BYPASS OIL FILTER

FIELD OF THE INVENTION

5 This invention relates to the field of oil filters and automotive technology.

BACKGROUND OF THE INVENTION

The typical engine oil filter system is a single pass, full flow filter that cleans the oil as it flows from the engine oil pump and then directs the flow to the oil galleys and other lubricated components of the engine. In order to more completely cleanse the oil, and to enable longer service life of the oil and engine components, additional, supplemental filtration in the form of by pass filtration is often utilized.

By pass filtration is achieved by diverting a small portion of an engines oil flow from a source under pressure, directing the flow slowly through a dense filter media and returning the bypass-filtered

oil to the engine sump. In most applications of full flow and bypass technology, each of these filters are separate units with the full flow filter mounted directly to the engine and the by pass unit mounted remotely, connected to the engine oil system via hoses or other plumbing.

Presently, there are several prior art designs for combining the full flow filter with a by pass filter all in the same housing.

In order to utilize these various combined full flow/by pass filter units one of two conditions must be met:

1. The engine and its oil filtration mounting apparatus must be designed for a specific combination filter unit. This combined full flow/by pass unit will not be readily useable on other engine designs. Thus the advantages offered by this type of full flow/by pass filter system are only available to a small and limited population of engines.

2. There are some generic types of full flow/by pass filter systems available that can be adapted to the general population of engines. However, these are after-market add-on products resulting in *ad hoc* mounting, often requiring special mounting brackets, remote filter head adapters and lengthy connecting hoses all of which are departures from the original engine design.

A further problem, especially with the first filters mentioned above, is that the rate of oil flow through the by pass portion of the combined full flow/by pass filter system must be taken as an article of faith. The separate, independent, and measurable flow of oil through the by pass portion cannot be observed or positively verified.

It is an object of this invention to provide a combination full flow/by pass engine oil filtration system that is easily adaptable to virtually all present day internal combustion engines, requiring no modification to said engine.

It is a further object of this invention to provide a means to readily measure and verify the separate oil flow through the by pass portion of the claimed filtration system.

BRIEF SUMMARY OF THE INVENTION

5 This invention is designed to provide a high-quality, dependable, combination full flow and bypass filter for lubrication fluids used in modern internal combustion engines.

 This invention combines two coaxial cylindrical oil filters with a novel recovery system for returning the oil from the bypass filter
10 to the engine sump, or other relatively low-pressure destination.

 The bypass filter removes essentially all solid contaminants from a fraction of the engine oil that enters the subject filter, and this clean fraction is returned to the engine oil supply, resulting in a steadily increasing level of oil cleanliness until a steady-state of cleanliness is
15 reached.

The present invention uses a non-venturi method of moving a fraction of the oil from the full flow through the bypass filter, unlike the previous state of the art filters. There are two embodiments of the present invention presented, a completely disposable system and
5 a replaceable system.

The replaceable system possesses a metal full-pass filter screen and a replaceable bypass filter element made of fiber, which can be removed from the filter canister and replaced with a new bypass filter element.

10 OBJECTS OF THE INVENTION

It is an object of this invention that the full flow and bypass filter canister system be compatible with existing engine mounts and require no special equipment be mounted on the engine.

It is an object of this invention that it work with any engine
15 using any standard oil pump and that it not need modifications to a

pressure regulator or a pressure relief valve to operate with standard engine oil pressures.

It is an object of this invention that positive fluid flow through both filters can be demonstrated at any engine speed, which

5 competing designs have failed to do.

BRIEF DESCRIPTION OF THE DRAWINGS

The construction and operation of the invention can be readily appreciated from inspection of the drawings that accompany this application, combined with the detailed specification to follow.

10 Figure 1 is an exterior view of the completely disposable embodiment.

Figure 2 is a cut-away drawing of the completely disposable embodiment of this invention.

15 Figure 3 is a cross-section of the completely disposable embodiment.

Figure 4 is a bottom view of the completely disposable embodiment of this invention

Figure 5 is an exterior view of the replaceable embodiment.

Figure 6 is a cutaway diagram of the replaceable embodiment.

5 Figure 7 is a top view of the replaceable embodiment.

Figure 8 is a cross-section of the replaceable embodiment.

Figure 9 is a bottom view of the replaceable embodiment.

Figure 10 is a chart showing measured output from the bypass filter as a function of filter inlet pressure

DETAILED DESCRIPTION OF THE INVENTION

Referring to Fig. 1, Fig. 2, Fig. 3, and Fig. 4, the invention¹⁰⁰ in its completely disposable version, the preferred embodiment, is shown. The general structure of the invention is a canister¹⁰¹ surrounding two coaxial filters, the bypass filter¹⁰² with a smaller diameter than the full flow filter¹⁰³. The bypass filter¹⁰² is placed within the hollow interior of the full flow filter¹⁰³ as shown. The full flow filter¹⁰³ is held against the full flow gasket¹⁰⁴ near the threaded engine mounting plate or "tap plate"¹⁰⁶ of the canister¹⁰¹ by a large spring¹⁰⁷ while the bypass filter is held against the bypass gasket by a small spring¹⁰⁸.

The operation of the filter is that fluid enters the canister¹⁰¹ through perforations¹⁰⁹ in the tap plate¹⁰⁶ and flows down the outer circumferential area¹¹⁹ of the canister, entering the full flow filter¹⁰³ circumferentially at the outside surface¹¹⁰ of the full flow filter¹⁰³ and proceeding towards the axis of the filter under

pressure. The fluid then enters the transition space¹¹¹ between the filters and most of that fluid exits the filter canister¹⁰¹ and directly enters the engine through the discharge opening¹¹² of the tap plate¹⁰⁶. A fraction of the oil in the transition space¹¹¹ enters the
5 bypass filter¹⁰² and exits the bypass filter¹⁰² into the bypass collection space¹¹³, whereupon it exits the filter canister through the bypass flow control orifice¹¹⁵ and discharge port¹¹⁴.

The bypass discharge port¹¹⁴ is connected via hose (not shown) to some low pressure point within the engine where oil can
10 be returned to the engine oil sump. The differential in pressure between the fluid entering the canister¹⁰¹ and the pressure at the destination of the hose from the bypass return port¹¹⁴ draws a measurable fraction of the total system oil flow through the denser bypass filter¹⁰². Eventually, all of the fluid passes through the
15 bypass filter¹⁰² and is cleaned to the dimensions allowed by the bypass filter¹⁰². It is a feature of this invention that the fluid is not

blended when it leaves the canister, but the bypass filter¹⁰² output is separately directed to the oil sump or other destination.

The bypass filter¹⁰² is comprised from a list of materials such as wound cotton and other dense fibers. The full flow filter¹⁰³ is
5 comprised of a material selected from a list including pleated paper and metal mesh.

An alternate embodiment of the present invention in Figs. 5 through 9 involves a disposable bypass filter element¹²⁰ and a cleanable filter screen¹²¹, made of steel in the preferred
10 instantiation of this embodiment. The filter canister system¹²² is held together at the end where the bypass return port¹²³ exits by means of screw threads¹²⁵, where the canister body¹²⁴ is connected to the canister bottom cap¹²⁶. When the canister bottom cap¹²⁶ is unscrewed, the cleanable filter screen¹²¹ can be lifted out and
15 cleaned, later to be replaced. The used bypass filter¹²⁰ can be replaced with a clean one, the bottom cap¹²⁶ screwed back on with

the entire unit remaining connected to the engine. As an alternative to the cleanable filter screen ¹²¹, a standard pleated paper full flow filter could be used in this design, making the filters completely replaceable.

5 The fluid flow path is similar to the preferred embodiment.

Fluid enters from the engine directly into the chamber¹⁴⁰ and then passes through several flow passages¹⁴¹ arrayed circumferentially around the full flow discharge opening¹⁴² at the base of the canister body¹²⁴, flows down the canister sides¹⁴⁴ and traverses the filter
10 screen¹²¹ to the transition space¹²⁹, where under differential engine pressure, a fraction of the fluid enters the bypass filter¹²⁰ and makes it through to the interior of the filter¹³¹, where it exits through the bypass return orifice¹³².

 The gasket¹⁴³ for the replaceable embodiment seals the
15 combined full flow/bypass filtration system to the engine filter mount (not shown). Gaskets ^{146,147} prevent the oil from taking a

short-cut from the chamber¹⁴⁰ to the transition space¹²⁹ or from the canister sides¹⁴⁴ to the transition space¹²⁹.

The four-bladed anti-blockage cap¹⁵⁰ on top of the bypass filter¹²⁰ prevents the bypass filter¹²⁰ from blocking oil flow
5 through the rest of the filter, through the filter screen¹²¹, in the event the bypass filter¹²⁰ breaks free of its mount¹⁵² inside the filter canister. If that should happen, without the four-bladed anti-blockage cap¹⁵⁰ present, the bypass filter¹²⁰ could plug the full flow discharge opening¹⁴², starving the engine for oil and causing
10 catastrophic engine failure.

The dimensions of the disposable filter's bypass return orifice¹¹⁵ and its equivalent on the replaceable embodiment are important to the effectiveness of the bypass filter^{102,120}, and the inventors have discovered that a dimension of 1 millimeter is
15 optimal for this outlet from the bypass filters^{102,120}.

It is a feature of this invention that this full flow and bypass filter canister system is compatible with existing engine mounts and requires no special equipment be mounted on the engine.

It is also a feature of this invention that positive fluid flow can
5 be demonstrated through both filters of the system at any engine speed, which competing designs have failed to do. In Fig. 10, the almost linear output of pure oil from the bypass filter¹⁰² through the bypass flow control orifice¹¹⁵ is shown for the preferred embodiment of the invention.

10 While the preferred embodiment and a first alternate embodiment of the invention have been described, modifications can be made and other embodiments of this invention realized without departing from the intent and scope of any claims associated with this invention.

15